Safety Data Sheet



Issue Date: 14-Jul-2014 Revision Date: 15-Jul-2014 Version 1

1. IDENTIFICATION

Product Identifier

Product Name Tac Spray Adhesive

Other means of identification

SDS # GI-014

UN/ID No UN1950

Recommended use of the chemical and restrictions on use

Recommended Use Adhesives.

Details of the supplier of the safety data sheet

Supplier Address Grayling Industries, Inc. 1008 Branch Drive Alpharetta, GA 30004

Emergency Telephone Number

Company Phone Number 1-800-635-1551

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White liquid Physical State Aerosol Odor Mint when wet

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Signal Word

Danger

Hazard Statements

Causes skin irritation

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Seek immediate medical attention/advice

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash it before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do not induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 48.88°C / 120°F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Propane	74-98-6	Proprietary
Acetone	67-64-1	Proprietary
Hexane	110-54-3	Proprietary
Dimethyl ether	115-10-6	Proprietary

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin Contact Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing

before reuse. Get medical attention if irritation occurs.

Inhalation If symptomatic, move to fresh air. Get medical attention if you feel unwell.

Ingestion Do not induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms May cause skin and eye irritation. Skin contact can lead to drying, defatting, itching, stinging

and irritation. Possible aspiration hazard. May cause nausea, vomiting, stomach ache, and diarrhea. May cause irritation to the mucous membranes and upper respiratory tract. Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion

or loss of coordination.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Aggravation of Pre-Existing Conditions: Eye, skin, and respiratory

disorders.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Dry chemical. Carbon dioxide (CO2). Water spray (fog).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Aerosols may rupture violently at temperatures above 120 F. Product is extremely flammable aerosol.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Container explosion may occur under fire conditions. Use water spray to keep containers cool. Use shielding to protect against bursting cans.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Use personal protection recommended in Section 8. ELIMINATE all ignition sources (no

smoking, flares, sparks or flames in immediate area).

For Emergency Responders Follow applicable OSHA regulations (29 CFR 1910.120).

Environmental Precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Absorb spillage with non-combustible, absorbent material. Clean up in accordance with all

applicable regulations. Dispose of in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Do not breathe vapors or spray mist. Wash face, hands, and any exposed skin thoroughly after handling. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Do not spray on an open flame or other ignition source. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Pressurized container: Do not pierce or burn, even after use. Remove all sources of ignition. Keep out of

the reach of children.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Do

not contaminate food or feed stuffs. Do not expose / store exceeding temperatures 48.88

°C / 120 °F.

Incompatible Materials Strong oxidizing agents, Acids, Reducing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors	
		(vacated) STEL: 1000 ppm	
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations

Ventilation systems. Ventilation must be adequate to maintain the ambient workplace

atmosphere below the exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses.

Skin and Body Protection Wear impervious gloves as required to prevent skin contact.

Respiratory ProtectionWear an appropriate NIOSH/MSHA approved respirator if ventilation is inadequate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Aerosol

AppearanceWhite liquidOdorMint when wetColorWhiteOdor ThresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH Not applicable

Melting Point/Freezing Point Not determined

Boiling Point/Boiling Range -42.22 - 70.55 °C / -44 - 159 °F

Flash Point -104.44 °C / -156 °F

Evaporation Rate Is faster than Butyl acetate (Water = 1)

Flammability (Solid, Gas) Extremely flammable aerosol

Upper Flammability Limits 18.0% Lower Flammability Limit 1.0%

Vapor PressureNot determinedVapor DensityHeavier than air

Specific Gravity 0.7011 (1=Water)

Water Solubility Negligible Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not established **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid contact with heat, sparks, electric arcs, other hot surfaces and open flames.

Incompatible Materials

Strong oxidizing agents, Acids, Reducing agents.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes skin irritation.

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Ingestion May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	-	-
67-64-1			
Propane	-	-	= 658 mg/L (Rat) 4 h
74-98-6			
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			
Dimethyl ether	-	-	= 308.5 mg/L (Rat) 4 h
115-10-6			

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

Revision Date: 15-Jul-2014

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Acetone		4.74 - 6.33: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia
67-64-1		Oncorhynchus mykiss mL/L		magna mg/L EC50 Static
		LC50 6210 - 8120: 96 h		12600 - 12700: 48 h Daphnia
		Pimephales promelas mg/L		magna mg/L EC50
		LC50 static 8300: 96 h		
		Lepomis macrochirus mg/L		
		LC50		
Hexane		2.1 - 2.98: 96 h Pimephales		1000: 24 h Daphnia magna
110-54-3		promelas mg/L LC50		mg/L ĖC50
		flow-through		

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Propane	2.3
74-98-6	
Acetone	-0.24
67-64-1	
Dimethyl ether	-0.18
115-10-6	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

<u>California Hazardous Waste Status</u> This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Hexane 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

IATA

UN/ID No UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1

<u>IMDG</u>

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Hexane	5000 lb		RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ

SARA 313

Ī	Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ī	Hexane - 110-54-3	110-54-3	Proprietary	1.0

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Acetone	X	X	X
67-64-1			
Propane	X	X	X
74-98-6			
Hexane	X	X	X
110-54-3			
Dimethyl ether	X	X	X
115-10-6			

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	4	1	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	4	1	В

Issue Date:14-Jul-2014Revision Date:15-Jul-2014Revision Note:New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet