Material Safety Data Sheet

May be used to comply with

OSHA's Hazard Communication Standard,

29 CFR 1910.1200. Standard must be

2) CITCIPIO. 1200. Standard Musico.

consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

IDENTITY (As Used on Label and List)

ISOPROPYL ALCOHOL 70% WITH WINTERGREEN

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name HYDROX LABORATORIES	Emergency Telephone Number 800-255-3924
Address (Number, Street, City, State, and ZIP Code)	Telephone Number for Information
825-B TOLLGATE ROAD	847-468-9400
ELGIN, IL 60123	Date Revised/Reviewed 12/09/08

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
ISOPROPYL ALCOHOL (CAS #67-63-0)	TWA 400 PPM	400 PPM	15 MIN CEILING (NIOSH) 500 PPM Rel TWA	
METHYL SALICYLATE (CAS #119-36-8)	NIOSH N/A	N/A	(10 HR.) 400ppm N/A	
ACUTE HEALTH HAZARD: 2 FIRE HAZARD: 3 REACTIVITY: 0	14/11	14/11	14/11	

Section III - Physical/Chemical Characteristics

Boiling Point Approx. 17	′0°F	Specific Gravity ($H_2O = 1$)	0.878 @ 20°C/20°C
--------------------------	------	---------------------------------	-------------------

Vapor Pressure (mm Hg.) Approx.	29 @ 20°C	Freezing Point Approx.	-32 to -50°C
Vapor Density (AIR = 1) Approx.	1.6	Evaporation Rate (Butyl Acetate = 1) Approx.	1.7
Solubility in Water	COM	PLETE.	
Appearance and Odor CL	EAR GREEN	LIOUID WITH METHYL SALICYL	ATE & ALCOHOL ODOR

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) Approx. 68° F - TOC	Flammable Limits	LEL 2.0	UEL 12.0	
Extinguishing Media CARBON DIOXID	DE, DRY CHEMICAL OR	ALCOHO	L FOAM FOG.	
Special Fire Fighting Procedures DILUTION OF BURNING L	IQUID WITH WATER W	VILL AFFE	CT EXTINGUISHME	ENT.
Unusual Fire and Explosion Hazards	NONE.			

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid AVOID HEAT, SPARKS AND OPEN FLAME.
	Stable	X	
Incompatibility			CYANATE, MONOMER AND ORGANO-METALLIC.
Hazardous Dec BURNING MA	omposition or B	Bypro CAR	educts BON MONOXIDE AND CARBON DIOXIDE CONTAMINATION.
Hazardous Dece BURNING MA Hazardous Polymerization	AY PRODUCE May Occur	Bypro CAR	ducts BON MONOXIDE AND CARBON DIOXIDE CONTAMINATION. Conditions to Avoid

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?	Eyes?
	YES	NEGLIGIBLE	YES	YES

Health Hazards (*Acute and Chronic*)

GENERALLY USED AS A RUBDOWN. VAPOR IRRITATES EYES. HIGH CONCENTRATION OF VAPOR CAN IRRITATE RESPIRATORY TRACT, IS ANESTHETIC AND MAY CAUSE CNS DEPRESSION.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
NOT A			
CARCINOGEN			
Signs and Symptoms	of Exposure		•
	GÍDDINESS, HEA	ADACHE, DIZZINES	SS AND NAUSEA.

Medical Conditions Generally Aggravated by Exposure

PRE-EXISTING AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

Emergency and First Aid Procedures

MOVE TO FRESH AIR. IF SWALLOWED, DO NOT INDUCE VOMITING AND CALL PHYSICIAN. FLUSH SKIN WITH WATER. FLUSH EYES WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEE A PHYSICIAN IMMEDIATELY

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled.

ELÎMINATE ALL SOURCES OF IGNITION. SMALL SPILLS SHOULD BE FLUSHED WITH LARGE QUANTITIES OF WATER. LARGER SPILLS SHOULD BE COLLECTED FOR DISPOSAL.

Waste Disposal Method

ATOMIZE INTO AN INCINERATOR WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE, AND LOCAL REGULATIONS.

Precautions to Be taken in Handling and Storing

DO <u>NOT</u> TAKE INTERNALLY. FĽAMMABLĚ LIQUID. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED.

Other Precautions N/A

Section VIII - Control Measures

Respiratory	Protection (<i>Specify Type</i>) AIR SUPPLII	ED MAS	SKS IN CONFINED AREAS.
Ventilation	Local Exhaust PREFERRED		Special
	Mechanical (General) ACCEPTABLE		Other
Protective Gl	oves R OR VINYL GLOVES	Eye Pr	otection CHEMICAL RESISTANT GOGGLES

Other Protective Clothing or Equipment
EYE BATH AND SAFETY SHOWERS.

Work/Hygienic Practices

HANDLE CAREFULLY; AVOID SPILLING. WASH HANDS BEFORE EATING, DRINKING OR SMOKING.

Disclaimer:

The contents of this MSDS are believed to be correct but do not purport to be all-inclusive and should only be used as a guide. Hydrox Laboratories, Inc. disclaims any express or implied warranty as to the accuracy of the above information and shall not be held liable for any direct, incidental or consequential damages resulting from the reliance on the above information.