

Version 3.0 Print Date 12/06/2013

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TREMLITE MASTIC - TROWEL GRADE 5 US GL

Product code : 346100 805

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST

Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

White. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.

Eyes : Slightly irritating.

Ingestion : May cause irritation to the mouth, throat and stomach.

Skin : Irritant effect may be delayed.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged or repeated exposure to butyl benzyl phthalate may cause reduced body weights and adverse effects on the liver, kidney, spleen, pancreas, and reproductive organs. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Acrylic polymer resin	NJ TSRN# 51721300-5025P	30.0 - 60.0
Water	7732-18-5	30.0 - 60.0
Calcium Carbonate (Limestone)	1317-65-3	15.0 - 40.0
Butyl benzyl phthalate	85-68-7	3.0 - 7.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

An **RPM** Company 1/6 346100 805



Version 3.0 Print Date 12/06/2013

REVISION DATE: 07/08/2012

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

Eve contact : Flush with water for 15 minutes. If irritation persists, get medical attention.

Skin contact: Wash with water. If irritation, rash or other disorders develop, get medical attention

immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available.

Method : Not available.

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : This product is not expected to burn under normal conditions of use. Use

that which is appropriate to the surroundings.

Hazardous combustion

products

Smoke, fumes.

Protective equipment for

firefighters

Not applicable. Product is not expected to burn.

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

Respiratory protection : Not required under normal conditions of use.

Hand protectionEye protectionUse safety glasses if eye contact is likely.

Protective measures : Use professional judgment in the selection, care, and use. Other equipment

not normally required.

Engineering measures : General ventilation is sufficient. Use local exhaust when the general

ventilation is inadequate.

An **PPII** Company 2/6 346100 805



Version 3.0 Print Date 12/06/2013

REVISION DATE: 07/08/2012

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Calcium Carbonate	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
(Limestone)		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Crystalline Silica	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
(Quartz)/ Silica Sand		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Non-sag gunnable paste

Color : White
Odor : Acrylate
pH : 8 - 9

Vapour pressure : Not available. Vapor density : Heavier than air Melting point/range : Not available. : < 32 °F, < 0 °C Freezing point Boiling point/range : Not available. Water solubility : Miscible Specific Gravity : 1.27 % Volatile Weight : 31 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Oxidizing agents. Strong acids. Strong bases.

SECTION 11 - TOXICOLOGICAL INFORMATION

Butyl benzyl phthalate, CAS-No.: 85-68-7

Acute oral toxicity (LD-50 oral) 13,500 mg/kg (Rat)



Version 3.0 Print Date 12/06/2013

REVISION DATE: 07/08/2012

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of

waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components:

Calcium Carbonate (Limestone) 1317-65-3 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered hazardous based on the

: Irritant Carcinogen

following criteria:

OSHA Flammability : Not Regulated

An **RPM** Company 4/6

/6 346100 805

Material Safety Data Sheet



TREMLITE MASTIC - TROWEL GRADE 5 US GL

Version 3.0 Print Date 12/06/2013

REVISION DATE: 07/08/2012

Regulatory VOC (less water and 20 g/l

exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components Calcium Carbonate (Limestone) 1317-65-3

Butyl benzyl phthalate 85-68-7

Acrylic polymer resin Penn RTK Components NJ TSRN# 51721300-5025P

> Water 7732-18-5 Calcium Carbonate (Limestone) 1317-65-3 Butyl benzyl phthalate 85-68-7

NJ RTK Components Acrylic polymer resin NJ TSRN# 51721300-5025P

> Water 7732-18-5 Calcium Carbonate (Limestone) 1317-65-3 Butvl benzvl phthalate 85-68-7

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and

Liability Act

DOT - Department of Transportation DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act TWA - Time Weighted Average

V - Volume

RPM Company 5/6 346100 805

Material Safety Data Sheet



TREMLITE MASTIC - TROWEL GRADE 5 US GL

Version 3.0 Print Date 12/06/2013

REVISION DATE: 07/08/2012

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

VOC - Volatile Organic Compound WHMIS - Workplace Hazardous Materials Information