

KRYLON DIV OF SHERWIN WILLIAMS -- 21-212 GLOSS WHITE NOW SPRAY PAINT -- 8010-00F047100

===== Product Identification =====

Product ID:21-212 GLOSS WHITE NOW SPRAY PAINT

MSDS Date:05/01/1992

FSC:8010

NIIN:00F047100

MSDS Number: BZCHF

=== Responsible Party ===

Company Name:KRYLON DIV OF SHERWIN WILLIAMS

Address:31500 SOLON RD

City:SOLON

State:OH

ZIP:44139-3908

Country:US

Info Phone Num:216-292-7400/800-832-2541

Emergency Phone Num:216-292-7400/800-832-2541

CAGE:KRYLO

=== Contractor Identification ===

Company Name:KRYLON DIV OF SHERWIN WILLIAMS

Address:6830 COCHRAN RD

City:SOLON

State:OH

ZIP:44139-3908

Country:US

Phone:216-292-7400/800-832-2541

CAGE:KRYLO

===== Composition/Information on Ingredients =====

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-1*

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

Other REC Limits:100 PPM

OSHA PEL:100 PPM

ACGIH TLV:100 PPM, SKIN

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 28%

OSHA PEL:2400 MG/CUM

ACGIH TLV:750 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL 3-ETHOXYPROPIONATE, PROPANOIC ACID, 3-ETHOXY-, ETHYL
ESTER *96-1*

CAS:763-69-9

RTECS #:UF3325000

Fraction by Wt: 3%

Ingred Name:TITANIUM DIOXIDE, TIO2 (SUSPECTED ANIMAL CARCINOGEN, IARC
GROUP 3) *96-1*

CAS:13463-67-7

RTECS #:XR2275000
 Fraction by Wt: 8%
 OSHA PEL:15 MG/CUM
 ACGIH TLV:10 MG/CUM (DUST)

Ingred Name:VOLATILE ORGANIC CONTENT: 82%/WT
 RTECS #:9999999V0

Ingred Name:PROPANE (DIMETHYLMETHANE) *96-1*
 CAS:74-98-6
 RTECS #:TX2275000
 Fraction by Wt: 14%
 Other REC Limits:1800 MG/CUM
 OSHA PEL:1000 PPM
 ACGIH TLV:SIMPLE ASPHYXIAN

Ingred Name:ISOBUTANE, 2-METHYLPROPANE
 CAS:75-28-5
 RTECS #:TZ4300000
 Fraction by Wt: 14%
 Other REC Limits:1000 PPM
 OSHA PEL:1800 MG/CUM
 ACGIH TLV:1000 PPM

Ingred Name:TOLUENE (IARC CARC- GROUP 3) *96-1*
 CAS:108-88-3
 RTECS #:XS5250000
 Fraction by Wt: 13%
 Other REC Limits:375 MG/CUM
 OSHA PEL:100 PPM
 ACGIH TLV:100 PPM
 EPA Rpt Qty:1000 LBS
 DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE *96-1*
 CAS:100-41-4
 RTECS #:DA0700000
 Fraction by Wt: 2%
 Other REC Limits:100 PPM
 OSHA PEL:435 MG/CUM
 ACGIH TLV:434 MG/CUM
 EPA Rpt Qty:1000 LBS
 DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
 Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
 Health Hazards Acute and Chronic:MAY CAUSE IRRITATION OF EYES, SKIN &
 RESPIRATORY SYSTEM & NERVOUS SYSTEM DEPRESSION. EXTREME
 OVEREXPOSURE MAY RESULT IN POSSIBLY DEATH. PROLONGED OVEREXPOSURE
 TO SOLVENTS MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY,
 BLOOD-FORMING CARDIOVASCULAR & REPROCUITIVE SYSTEMS. (SEE SUPP)
 Explanation of Carcinogenicity:NONE
 Effects of Overexposure:IRRITATION, UNCONSCIOUSNESS, HEADACHE,
 DIZZINESS, NAUSEA, LOSS OF COORDINATION, REDNESS, ITCHING, BURNING
 SENSATION

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP

WARM & QUIET. SKIN: WASH AREA THOROUGHLY W/SOAP & WATER. EYES:
FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. OBTAIN MEDICAL
ATTENTION IN ALL CAS ES.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:<0F

Lower Limits:1

Upper Limits:12.8

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:WEAR FULL PROTECTIVE EQUIPMENT W/SCBA. WATER
SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE
PREFERRED. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE DUE TO THE
BUILDUP OF PRESSURE WHEN EXPOSED TO EXTREME HEAT. VAPORS WILL
ACCUMULATE READILY & MAY IGNITE EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENTILATE &
REMOVE W/INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM IGNITION SOURCES. DON'T
PUNCTURE/INCINERATE/EXPOSE TO TEMP >120F. USE APPROVED BONDING &
GROUNDING PROCEDURES. KEEP OUT OF REACH OF CHILDREN

Other Precautions:DURING USE & UNTIL ALL VAPORS ARE GONE, KEEP AREA
VENTILATED, DON'T SMOKE, EXTINGUISH FLAME/IGNITION SOURCE. DON'T
TAKE INTERNALLY. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT
W/SKIN & EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE CAN'T BE CONTROLLED 1

Evaporation Rate & Reference:FASTER THAN ETHER

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, ELECTRICAL
EQUIPMENT, TEMPS >120F, SUNLIGHT/OTHER IGNITION SOURCES.

Hazardous Decomposition Products:BY FIRE: CO2, CO

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MUST BE TESTED FOR IGNITABILITY TO
DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. DON'T
INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IAW/LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.