

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

HEALTH HAZARD RATING HMIS NFPA
HEALTH 1
FLAMMABILITY 4
REACTIVITY 3
PERSONAL PROTECTION B

HAZARD INDEX
SEVERE HAZARD 4
SERIOUS HAZARD 3
MODERATE HAZARD 2
SLIGHT HAZARD 1
MINIMAL HAZARD 0

PERSONAL PROTECTION
A GLASSES
B GLASSES & GLOVES
C GLASSES, GLOVES & APRON
D FACE SHIELD, GLOVES & APRON
E GLASSES, GLOVES & RESP.

MANUFACTURER IDENTIFIED BY:
Paris Associates

EMERGENCY TELEPHONE NUMBER:
(800) 451-8346

REVISION DATE:
10/22/01

INFORMATION TELEPHONE:
(800) 321-1128

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER 86507 PRODUCT CLASS Aerosol-Paint
PRODUCT NAME GMC White

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	%	ACGIH	OSHA	OSHA	OSHA
			TLV TWA	FEL	PEL	TLV STEL
			PPM	PPM	MG/MP3	MG/MP3
Acetone	67-64-1	20.40	500	1000	2400.0	N/A
Propellant: Propane	74-98-6	13.70	2500	1000	1800.0	N/A
Titanium Dioxide	13463-67-7	9.30	N/A	N/A	15.0	N/A
n-Butane	106-97-8	9.20	800	N/A	N/A	N/A
Xylene	1330-20-7	6.40	100	100	435.0	N/A
Glycol Ether EP	2807-30-9	3.70	25	25	N/A	N/A
Methyl Iso-butyl Ketone	108-10-1	3.30	50	100	410.0	N/A
Methyl Propyl Ketone	107-87-9	2.30	200	200	700.0	N/A
Ethyl Benzene	100-41-4	1.50	100	100	435.0	N/A
SC-100 Solvent	64742-95-6	1.20	300	300	1350.0	1800.0

Pressurized Container 45-60 PSI

- Ⓢ Subject to reporting under SARA Title III. See Section IX - Special Precautions
! Subject to warning under CA Proposition 65. See Section IX - Special Precautions

SECTION III - PHYSICAL DATA

BOILING POINT (degrees F): -44 F
VAPOR DENSITY: Heavier than air.
VOLATILE (By Volume) 4.10 lbs/gal
ODOR AND APPEARANCE: Solvent odor, white color

EVAPORATION RATE: Faster than ether.
WEIGHT PER GALLON (LBS): N/A

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION:

OSHA CLASS N/A
DOT CLASS ORMD

INCO CLASSIFICATION NUMBER:

N/A

FLASH POINT (Degrees F): -4

(lowest flash point of any ingredient, not of product as whole)

LEL: 1.0%

NFPA FIRE PROTECTION LEVEL: 3

AEROSOL PRODUCT: Treat as cylinder of compressed gas.

EXTINGUISHING MEDIA:

FOAM CO2 ALCOHOL FOAM DRY CHEMICAL WATER FCG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Temperature above 120° F may cause can bursting.

SPECIAL FIREFIGHTING PROCEDURES:

Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

U.M. CLASSIFICATION:

PER DOT N/A
PER HAZO N/A

IAEA CLASSIFICATION:

N/A

METHOD: Clew Closed Cup

UEL: 12.8%

VOLATILE ORGANIC COMPOUNDS: 43%

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

Eyes: Irritation, redness, tearing, blurred vision. Skin: Moderate irritation, dermatitis. Breathing: Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and even asphyxiation. Swallowing: Gastro-intestinal irritation, nausea, vomiting, diarrhea.

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT SKIN ABSORPTION EYE CONTACT INHALATION INGESTION

MEDICAL CONDITIONS PRONE TO OVEREXPOSURE:

Fumes and gases can be dangerous to your health. Aggravation of pre-existing respiratory or allergic conditions may occur in some workers.

TARGET ORGANS AFFECTED:

Vapors: Irritating to eyes and respiratory tract.
Direct Contact: Irritating to skin and eyes.

CARCINOGENICITY:

None of the components in this chemical are listed by IARC, NTP or OSHA as a carcinogen.

EMERGENCY AND FIRST AID PROCEDURES:

Remove to fresh air, irrigate eyes, contact physician if necessary.

86507

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

SECTION VI - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:

By open flame: CARBON MONOXIDE, CARBON DIOXIDE.

CONDITIONS TO AVOID:

Pressurized containers may rupture above 120°F.

INCOMPATIBILITY (MATERIALS TO AVOID)

None Known.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition, ventilate. Avoid breathing vapors and remove with inert absorbent.

WASTE DISPOSAL METHOD:

Dispose of product in accordance with local, county, state, and federal regulations. Do not puncture or incinerate container. Do not reuse container. Wrap container and place in trash collection.

SECTION VIII - SPILL OR LEAK PROCEDURES

RESPIRATORY PROTECTION:

If airborne concentrations exceed recommended exposure limits, a suitable NIOSH respirator should be worn.

VENTILATION:

If current ventilation practices are not adequate in maintaining airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required.

PROTECTIVE GLOVES:

Required for prolonged or repeated contact.

EYE PROTECTION:

Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT:

Eye wash station and safety showers should be available.

HYGIENIC PRACTICES:

Wash Hands before eating or using the washroom.

Smoke in SMOKING AREAS ONLY.

MATERIAL SAFETY DATA SHEET
ESSENTIALLY SIMILAR TO OSHA FORM 174

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Avoid eye contact and excessive skin contact.

OTHER PRECAUTIONS

All ingredients marked with an (C) symbol are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFRPart372.

Date of Preparation 1/14/00

RESPONSIBLE PERSONS:
Parts Associates

"Final determination of suitability of the chemical(s) is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. NO REPRESENTATIONS OF WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS."

ACGIH AM. Conference of Governmental Indust. Hygienists
 CNS Central Nervous System
 HMIS Hazardous Materials Identification System
 IATA International Air Transport Association
 LEL Lower Explosive Level
 N/A Not Currently Available
 NTP National Toxicology Program
 PEL Permissible Exposure Levels
 STEL Short Term Exposure Limit
 TWA Time Weighted Average
 TE Trace Element(s)

CAS Chemical Abstract Service
 DOT Department of Transportation
 IARC International Agency for Research on Cancer
 IMCO International Maritime Commission Organization
 MG/M³ Milligrams per Cubic Meter
 NFPA Nation Fire Protection Agency
 OSHA Occupational Safety & Health Administration
 PPM Parts Per Million
 TLV Threshold Limit Value
 UEL Upper Explosive Level