

TECHNICAL INFORMATION GUIDE

POXYLUBE® CP-200

AIR DRYING SOLID FILM LUBRICANT

Approved for Medeco® Locks

SERIES L200

SANDSTROM

PRODUCTS COMPANY

PORT BYRON, IL 61275 • (309) 523-2121

1-800-747-1084 FAX # 1-309-523-3912

www.sandstromproducts.com

DESCRIPTION

Sandstrom **POXYLUBE® CP-200** lubricates without the contamination of dust or debris pick-up associated with oils or other liquid lubricants. The dry film clings to all metallic and non-metallic surfaces and is not affected by water or normal temperature fluctuations. Ideal for use on locks, hinges, latches, pins, sliding surfaces (such as drawers), valves, seals, rollers, casters, levers and cranks, pipe and threaded connections, guides and water pumps.

A unique stainless steel spray needle is available as an optional attachment for easier insertion and for those hard to reach areas.

OUTSTANDING FEATURES/BENEFITS

- Easy to apply; won't run off or drip under heat or pressure and does not evaporate.
- Dries quickly
- Self bonding - bonds to most surfaces with minimum surface preparation.
- Formulation contains non-volatile solids and bonding agent which are non-migratory.

TYPICAL USES

Use Sandstrom **POXYLUBE® CP-200** to:

- Retard and resist corrosion, water, dust and dirt build-up and wear
- Prevent seizure; allows increased threaded joint tightening with the same applied torque for easier disassembly.

COMPOSITION AND PHYSICAL PROPERTIES

NET WEIGHT PER GAL	6.0 ± 0.5 lbs per gallon	STORAGE CONDITIONS	Store at temperatures below 100°F
NONVOLATILES	3.55 ± 2.0% (by Weight)	VOC (Theoretical)	5.52 lbs. per gallon
OPERATING TEMP. RANGE	-100°F to +350°F	ODOR	Strong Solvent
LUBRICATIVE PIGMENT	Fluorotelomer Dispersion	SHELF LIFE	2 years from date of shipment (BE SURE TO ROTATE STOCK)
COLOR	Colorless		

APPLICATION INSTRUCTIONS

1. Clean surface, remove excess oil, grease, scale and rust.
2. **POXYLUBE® CP-200** contains pigment which tends to settle out. Shake the aerosol cans thoroughly before and during use.
3. Dries rapidly for immediate use (1-3 minutes).
4. Clean up with Isopropyl Alcohol.

WARNINGS

FLAMMABLE! Keep away from heat, sparks and open flame. **AVOID BREATHING VAPORS!** Use with adequate ventilation. If swallowed, **DO NOT** induce vomiting. Contact physician. Material Safety Data Sheet has complete warnings and necessary precautions for proper use of this product. If you do not have an MSDS, contact your Sandstrom Representative.

IMPORTANT NOTICE TO BUYER / WARRANTY AND LIMITATIONS ON OUR LIABILITY

We warrant our products to be free of manufacturing defects, and that they meet our current published physical properties and specifications. All information and suggestions presented are rendered gratis and is accurate to the best of our knowledge. They are based on technical data which we believe to be reliable, and are intended for use by persons having skill and "know-how," at their own discretion and risk. Prior to use, customers are cautioned to determine the suitability of our products for any given application through their own testing. **NO WARRANTY IS MADE, EXPRESS OR IMPLIED, REGARDING SUCH INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS OBTAINED FROM ITS USE OR THAT OUR PRODUCT SHALL BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. SUCH STATEMENTS ARE NOT INTENDED TO SUGGEST INFRINGEMENT OF ANY PATENT.** Since conditions of use of our products are beyond our control, all suggestions and statements are made without guarantee, warranty or other responsibility, express or implied, on our part. We assume no responsibility for results obtained, or damages incurred, from their use beyond replacing material proved to be defective or refunding the purchase price of such material at our option. Acceptance of delivery of our product means you have accepted the terms of this warranty, whether or not purchase orders or other documents state terms that vary from this warning. No seller is authorized to make any representations or warranty or assume any other liability on our behalf with any sales of our products. © 2/1/98 SANDSTROM PRODUCTS COMPANY 2/6/2012